

Speaker: [Professor Mariusz Martyniuk](#)

Facility Manager, ANFF WA Node
Research Professor
Microelectronics Research Group
University of Western Australia



Date: Monday 2 September 2019

Time: 11.00 am

Venue: Room 1.08 QMF building (N74), Griffith University, Nathan Campus

Title: **MEMS-based optical filters for spectrally adaptive remote sensing in infrared and terahertz spectral ranges**

Abstract:

Improving current state-of-the-art infrared (IR) detector and imaging focal plane array (FPA) technologies includes adding so-called multi-colour capability, which allows real-time spectral information to be gathered from multiple wavelength bands. Multi-spectral imaging results in improved target recognition and is applicable to numerous remote sensing spectroscopy/imaging applications. In order to provide a reduced size, weight and power (SWaP) solution, a micro-electromechanical systems (MEMS) based electrically tuneable adaptive filter technology has been developed for important IR and emerging THz wavelength bands of the electromagnetic spectrum. We present the development of MEMS-based optical filter technologies capable of adaptive low-voltage electrostatic tuning of spectral selectivity in wavelength bands spanning from visible, through infrared, to terahertz parts of the electromagnetic spectrum. Figure 1 schematically presents the adopted approach capable of delivering on-chip remote hyper/multi-spectral sensing by obtaining narrow-band spectral sensitivity utilising a tuneable MEMS optical filter fabricated directly on an infrared detector. The technology has been demonstrated to operate in the near infrared (NIR, 0.7 – 1.7 μm), the short-wave infrared (SWIR, 1.4 – 2.5 μm), mid-wave infrared (MWIR, 3 – 5 μm), long-wave infrared (LWIR, 8 – 12 μm), and terahertz ranges (~ 1 THz or ~ 300 μm). In LWIR, we report spatial peak wavelength selectivity variation of less than 1.2% across 200- μm \times 200- μm optical imaging areas, exceeding the requirements for passive multispectral thermal imaging applications (spectral characteristics across the entire tuning range of 8.5–11.5 μm : peak transmission above 80%, full-width at half-maximum of spectral passband of ~ 500 nm, and out-of-band rejection greater than 40:1). Utilising the merger of the developed MEMS capabilities with metamaterial concepts as depicted in Fig. 1(c), shows suitability to extend the filtering capabilities towards the longer THz wavelength band by demonstration of wavelength absorption selectivity tuning across a 16 μm (60GHz) wide spectral band for 300 μm wavelength (1 THz) radiation. The presented MEMS-based optical filters are applicable for hybridisation into technologies capable of mechanically robust field-portable spectroscopic chem/bio sensing, as well as for UAV-based imaging and remote sensing applications.

For enquiries, please contact Mrs Lacey Shaw: l.shaw@griffith.edu.au

ALL WELCOME